


## SPECIFICATIONS


DIAMETER:	8" (203.4 mm)
SENSITIVITY (2.83 V @ 1 m):	91 dB
POWER HANDLING:	200 W <sub>RMS</sub>
FREQUENCY RESPONSE:	50 ~ 1,000 Hz
NOMINAL IMPEDANCE:	4 OHMS
VOICE-COIL DIAMETER:	1.5" (38.0 mm)
DIMENSIONS:	




## THIELE-SMALL PARAMETERS

VOICE COIL DC RESISTANCE:	$R_{EVC}$ (OHMS) . . . . .	3.10
VOICE COIL INDUCTANCE @ 1 kHz:	$L_{EVC}$ (MH) . . . . .	2.10
DRIVER RADIATING AREA:	$S_D$ (IN <sup>2</sup> ) . . . . .	31.02
	$S_D$ (CM <sup>2</sup> ) . . . . .	201.00
MOTOR FORCE FACTOR:	$BL$ (TM) . . . . .	8.28
COMPLIANCE VOLUME:	$V_{AS}$ (FT <sup>3</sup> ) . . . . .	0.94
	$V_{AS}$ (LITERS) . . . . .	22.20
SUSPENSION COMPLIANCE:	$C_{MS}$ (μM/N) . . . . .	387.00
MOVING MASS, AIR LOAD:	$M_{MS}$ (GRAMS) . . . . .	30.31
MOVING MASS, DIAPHRAGM:	$M_{MD}$ (GRAMS) . . . . .	28.67
FREE-AIR RESONANCE:	$F_S$ (Hz) . . . . .	46.47
MECHANICAL Q:	$Q_{MS}$ . . . . .	7.54
ELECTRICAL Q:	$Q_{ES}$ . . . . .	0.40
TOTAL Q:	$Q_{TS}$ . . . . .	0.38
MAGNETIC-GAP HEIGHT:	$H_{AG}$ (IN) . . . . .	0.24
	$H_{AG}$ (MM) . . . . .	6.00
VOICE-COIL HEIGHT:	$H_{VC}$ (IN) . . . . .	0.59
	$H_{VC}$ (MM) . . . . .	15.00
MAXIMUM EXCURSION:	$X_{MAX}$ (IN) . . . . .	0.18
	$X_{MAX}$ (MM) . . . . .	4.50


## IMPEDANCE CURVE




## INFINITE Baffle FREQUENCY RESPONSE @ 2.83 V




## INFINITE Baffle EXCURSION/GROUP DELAY @ 35 W




## SEALED BOX VOLUME




## VENTED BOX VOLUME




## SEALED FREQUENCY RESPONSE @ 2.83 V




## VENTED FREQUENCY RESPONSE @ 2.83 V




## SEALED EXCURSION/GROUP DELAY @ 100 W




## VENTED EXCURSION/GROUP DELAY @ 150 W




## SEALED BANDPASS BOX VOLUME



## SEALED BANDPASS FREQUENCY RESPONSE @ 2.83 V



## SEALED BANDPASS EXCURSION/GROUP DELAY @ 125 W



## NOTES